


CAPACITIVE PROXIMITY SENSORS SPECIFICATIONS



SENSING DISTANCE	1-15 mm adjustable	1-15 mm adjustable	1-30 mm adjustable	1-30 mm adjustable	1-40 mm adjustable
OPERATING TEMPERATURE	-25 °C - +70 °C				
SENSING FACE MATERIAL	PBT Plastic	PTFE	PBT Plastic	PTFE	PTFE
HOUSING MATERIAL	PBT Plastic	Stainless Steel	PBT Plastic	Stainless Steel	Stainless Steel
PART NUMBERS					
DC 3-wire 10-30 V PNP - Open	CCP2-1815P-A3U2	CCU2-1815P-A3U2	CCP2-3030P-A3U2	CCU2-3030P-A3U2	CCU2-3240P-A3U2
DC 3-wire 10-30 V PNP - Closed	CCP2-1815P-B3U2	CCU2-1815P-B3U2	CCP2-3030P-B3U2	CCU2-3030P-B3U2	CCU2-3240P-B3U2
DC 3-wire 10-30 V NPN - Open	CCP2-1815N-A3U2	CCU2-1815N-A3U2	CCP2-3030N-A3U2	CCU2-3030N-A3U2	CCU2-3240N-A3U2
DC 3-wire 10-30 V NPN - Closed	CCP2-1815N-B3U2	CCU2-1815N-B3U2	CCP2-3030N-B3U2	CCU2-3030N-B3U2	CCU2-3240N-B3U2
AC 20-240 V AC - Open	CCP2-1815A-A3L2	CCU2-1815A-A3L2	CCP2-3030A-A3L2	CCU2-3030A-A3L2	CCU2-3240A-A3L2
AC 20-240 V AC - Closed	CCP2-1815A-B3L2	CCU2-1815A-B3L2	CCP2-3030A-B3L2	CCU2-3030A-B3L2	CCU2-3240A-B3L2

NOTE: Specifications subject to change without notification.

*Flatpack, M8 and M12 sizes available.

CAPACITIVE SENSORS ARE THE BEST CHOICE FOR THE RELIABLE DETECTION OF LIQUIDS, BULK SOLIDS, PLASTICS, POWDERS, PELLETS AND PASTES WHERE A NON-CONTACT SOLUTION IS REQUIRED.

